

# 120 PLUS

DIGITAL WEIGHT INDICATOR



**RICE LAKE**<sup>TM</sup>  
WEIGHING SYSTEMS

Commitment Beyond Measurement<sup>®</sup>

[www.ricelake.com](http://www.ricelake.com)



# 120 PLUS DIGITAL WEIGHT INDICATOR




## Where Economy and Performance Meet

With the 120 Plus, there is no need to sacrifice quality for price. This digital weight indicator is designed to be a reliable, cost-effective solution for material handling or shipping and receiving applications.

The 120 Plus drives up to four 350Ω load cells. Three-stage digital filtering provides stable, accurate weight data. The 120 Plus's tactile front panel and easy-to-read LCD display help to make scale operations effortless. Two independent communication ports provide full EDP and print ticket programmability.

## A Combined Effort

Purchase the 120 Plus alone, or buy it with one of our quality bench or floor scales. We've paired the 120 Plus with a bench scale as an economic bundled option. The 17" x 21" stainless steel platform is an ideal size for a range of applications.



Additionally, we offer a floor scale and indicator package that combines the 120 Plus with the Summit 3000 Floor Scale. They arrive at your location corner trimmed and calibrated for 5000 divisions.



Program a ticket format with the 120 Plus.  
Use up to 180 characters.

## Standard Features

- Large .8" (20 mm) LCD display with back light
- Powered with rechargeable battery or wall adapter
- Power save feature for 700 hours of battery life
- Two setpoints with delay and timer selections
- Three digital inputs
- Ten stored tare values
- Display hold based on 3 second average
- Tilt stand
- Time and date

## Options/Accessories

- Revolution III Scale Software
- Additional operating manual

## Specifications

<b>Line Voltages:</b>	115 / 230 VAC with AC adapter
<b>Power Consumption:</b>	60 hours with (1) 350 40 hours with (4) 350
<b>Excitation Voltage:</b>	5 ± 0.5 VDC, 4 x 350Ω load cells
<b>Analog Signal Input Range:</b>	0.6 mV/V - 3.0 mV/V
<b>Analog Signal Sensitivity:</b>	0.3 μV/graduation minimum, 1.5 μV/grad recommended
<b>Resolution:</b>	Internal resolution: 1,000,000 internal graduations
<b>Display Resolution:</b>	100,000 displayed graduations
<b>Measurement Rate:</b>	30 per second
<b>System Linearity:</b>	Within 0.01% of full scale
<b>Circuit Protection:</b>	RFI, EMI, ESD protected
<b>Serial Output:</b>	7 or 8 data bits; even, odd or no parity
<b>Printer Port:</b>	Output-only RS-232 or active 20 mA current loop
<b>EDP Ports:</b>	Full duplex RS-232 (1200-38400 bps)
<b>Display:</b>	0.8" (20 mm), 6-digit LCD with backlight display, 7-segment, number digits
<b>Status Annunciators:</b>	Designators for: center of zero, stand still, gross, net, lb, kg, oz, g, battery, setpoints
<b>Keyboard:</b>	18-key flat membrane panel, tactile feel
<b>Operating Temperature:</b>	-10°C to 40°C/14°F to 104°F (legal) -10°C to 50°C/14°F to 122°F (industrial)
<b>Warranty:</b>	1-year limited warranty

## Approvals Pending



Pending\*

Measurement  
Canada  
Approved

Pending



Pending



Pending

Your Rice Lake Weighing Systems distributor is:

**RICE LAKE**™  
WEIGHING SYSTEMS  
Commitment Beyond Measurement®



230 W. Coleman St. • Rice Lake, WI 54868 • USA  
TEL: 715-234-9171 • FAX: 715-234-6967 • [www.ricelake.com](http://www.ricelake.com)

© 2008 Rice Lake Weighing Systems PN 105278 5/08  
Specifications subject to change without notice